Honeywell Audiovisuals is a strategic business unit of Honeywell Life Safety under global Fortune 500 Honeywell International Inc. Honeywell Audiovisuals is specialized in designing, developing, manufacturing and selling public address and voice alarm systems. Being an expert in acoustic excellence, our mission statement is to provide our customers who need sound and voice propagation a better, safer, and a more efficient public address management system and solution.

As a global leading manufacturer, Honeywell Audiovisuals is always in pursuit of innovations and driven by the most cutting edge technologies. With an experienced team of R&D elites working in world-class laboratories, Honeywell Audiovisuals implements the most efficient operation and strictest quality control system in the industry. Our advanced design concepts focus on networkability, modularization, and user-friendliness. "Empower the Sound" is our promise to create a greater value to our customers around the world.





Honeywell Audiovisuals
hav.international@honeywell.com

Subject to change without notice LEADWAYSPK\_V4.2\_EN Oct, 2014 © 2014 Honeywell International Inc.

### **LEADWAY SERIES**





# **Extend Leadership into Acoustic Excellence**

High Quality Loudspeakers for Public Address and Voice Alarm Systems



## Pendant Loudspeaker

Pendant loudspeaker of Leadway series adopts elegant design and convenient installation method, which can be hanged on the ceiling with the accessory cables. As wide as 360 degree sound coverage makes it the best choice for most indoor applications.



# 06 Pendant Loudspeaker



### **ABS Pendant Loudspeaker**

- Suitable for speech and music reproduction
- Simple power setting
- Easy installation
- Robust fire resistant ABS enclosure
- Supplied with a 2m long fire resistant cable
- CE and RoHS compliant





SPECIFICATIONS	L-PPP20A
Max power	30W
Rated power	20W
Power taps @ 100V	20W / 10W / 5W
SPL at 20W/1W (100Hz - 6kHz,1m)	103dB / 90dB
Frequency response (-10dB)	80Hz - 12kHz
Dispersion angle (1KHz/-6dB)	Horizontal 360°, Vertical 140° - 160°
Rated input voltage	100V / 70V
Rated impedance	500Ω / 1ΚΩ / 2ΚΩ
Connection	Wire Cable
Dimensions (D x L)	Ф254
Speaker Size	8"
Weight	2.2kg
Color	White
Material	ABS