


HADC-2305PIV 1080P AHD Vandal IR Dome Cameras

Featuring the advanced Analog High Definition (AHD) video technology, HADC-2305PIV is a HD analog camera which provides 1080P (1920 x 1080) sharp, high definition images. The AHD technology ensures real-time and non compressed signal transmission via coaxial cable, which significantly reduces installation cost and provides much sharper images without video quality loss.

Market Opportunities

The HADC-2305PIV cameras are cost effective surveillance Solutions suitable for both indoor and outdoor applications, including schools, colleges, hotels, hospitals, commercial sites, retail stores, warehouses, banks and so on. Featuring 3.6mm & 2.8-12mm built-in lens, 1080P resolution, TDN function and IR night vision. It is also ideal for easy and cost-effective upgrade of existing analog system to high definition surveillance.



KEY FEATURES

- 1080P real time high resolution
- CMOS progressive scan
- True Day/Night Capability
- Minimum illumination: 0 Lux (IR on)
- TDN (IR-Cut), AWB, AGC, Defog
- 3.6mm & 2.8-12mm lens
- IR distance: Upto 30 meters
- Power:12VDC
- Vandal resistant
- Dual Output AHD & CVBS

HADC-2305PIV

1080P AHD Vandal IR Dome Cameras


SPECIFICATIONS

Part Code	HADC-2305PIV
System	
Video Standard	PAL/NTSC
Scanning System	Progressive
Image Sensor	1/2.9" SONY CMOS Sensor
Resolution	1080P
Number of Pixels	1920 (H) x 1080 (V)
Minimum Illumination	0.005Lux BW, 0Lux IR
Video Output	AHD BNC, CVBS terminal
Video Frame Rate	25/30 fps (PAL/NTSC)
Sync System	Internal
Automatic Electronic Shutter	1/25s ~ 1/50,000s(PAL), 1/30s ~ 1/60,000s(NTSC)
Lens Type	2.8mm ~ 12mm
IR LEDS	36 LEDS
IR Illumination Distance	Upto 30m, depending on scene reflectance
SNR	≥50 db
Day/Night	Auto with ICR
Automatic Gain Control	Auto
White Balance	Auto/Manual
Digital Noise Reduction	Auto (3DNR)
WDR	DWDR (ON/OFF)
OSD	Yes
Electrical	
Input Voltage	DC12V ± 10%, 700mA
Power Consumption	8.4W ± 10%
Mechanical	
Dimensions	131 x 93(H)mm
Weight	800g
Construction	Housing: Vandal resistant; Color: Semi-white
Connectors	Video output: AHD BNC connector; CVBS terminal, Power input: 2.1mm plug
Environmental	
Operating Temperature	-10°C to 50°C
Relative Humidity	10% to 95%, non-condensing
Regulatory	
Certification	CE
System Compatibility	
Compatible DVR	AHD DVR

Note: Honeywell reserves the right, without notification, to make changes in product design and/or specifications.

DIMENSIONS

HADC-2305PIV



ORDERING INFORMATION

HADC-2305PIV	1/2.9" SONY CMOS Sensor, 1080P AHD, TDN, DNR, DWDR, 36 LED, 2.8~12mm, IR Vandal Dome Camera, 12 VDC with OSD, PAL
HADC-2305NIV	1/2.9" SONY CMOS Sensor, 1080P AHD, TDN, DNR, DWDR, 36 LED, 2.8~12mm, IR Vandal Dome Camera, 12 VDC with OSD, NTSC

For more information

HBT-IndiaBuildings@Honeywell.com

Honeywell HBT India Buildings

Unitech Trade Centre, 5th Floor, Sector – 43
Block C, Sushant Lok Phase – 1
Gurgaon – 122002, Haryana, India
Tel: +91 124 4975000
www.honeywell.com