

## 4-/8-/16-/32-Channel ENVRs

HEN04103L/ HEN08103L

HEN16103L/ HEN32103L

Introducing Honeywell's Performance Series Embedded NVRs, our newest affordable, fully-featured NVRs offer Ultra 4K HD video resolution. Choose between a 4-, 8-, 16- or 32-channel NVR, with multiple hard drive options and up to 12 TB of internal storage, for an ideal and flexible solution to fit your surveillance needs.

### Fully-featured NVRs

- High decoding capability for Ultra 4K HD viewing and recording
- View 4/8/16/32 channels simultaneously with synchronized real-time playback on your monitor (depending on your model)
- Up to 8 MP (4K) resolution live view, preview and playback
- Up to 8 channels at 1080p H.265/H.264 decoding

### Dynamic, Accessible Monitoring

- Mobile apps provide anytime, anywhere access for both Apple® and Android™ devices (smartphones, tablet computers, and laptops)
- Protect the NVR's video and network setup with password-protected access
- Conceal up to 4 areas of a scene from viewing and recording

### Convenient, Flexible Storage Options

- Internal storage supports 2 HDDs expandable up to 12 TB (6 TB each)
- Store video clips and snapshots to external storage, such as the client's PC, through the Internet connection
- Store video clips and snapshots to external network storage servers, such as an FTP site
- Store video clips and snapshots to a USB memory device



HEN16103L/ HEN32103L



HEN04103L/ HEN08103L

### Easy to Use

- The Quick wizard makes setup fast and easy
- Quick installations utilizing an intuitive NVR design and easy-to-understand quick installation guides
- Simple remote configuration and firmware updates through the Honeywell Viewer web client and the Honeywell Config tool

### Market Opportunities

The flexible storage options, high recording and networking performance of the Embedded NVRs make these NVRs perfect for a wide range of security applications.

## FEATURES & BENEFITS


These fully featured attractive cameras are perfect for outdoor installations that require excellent picture quality at minimal bandwidth while offering maximum protection against dust, dirt, and water. Boasting a sleek, modern design and offering two different lens options, the cameras are suited for a wide range of applications.

- |  |   |   |   |  |
|--|---|---|---|--|
| <ul style="list-style-type: none"> <li>• H.265/H.264 codec decoding</li> <li>• HDMI/ VGA simultaneous video output</li> <li>• UL listed</li> </ul> | <ul style="list-style-type: none"> <li>• Supports up to 4 alarm input channels and 2 alarm relay output channels</li> <li>• Supports sending notifications through email, FTP, and/or HTTP</li> </ul> | <ul style="list-style-type: none"> <li>• Supports recording a video clip of events for distribution</li> <li>• Supports uploading still images at the time of the event through email and/or FTP</li> </ul> | <ul style="list-style-type: none"> <li>• Configurable to automatically detect and respond to motion in the scene, alarm inputs, and network failure or tampering</li> <li>• Maximum incoming bandwidth of 200 Mbps</li> </ul> | <ul style="list-style-type: none"> <li>• Supports visual or auditory notifications (a flashing light, bell, or siren)</li> <li>• Supports Smart Face detection search</li> </ul> |
|--|---|---|---|--|


# 4-/8-/16-/32-Channel ENVRs

## SYSTEM DIAGRAM

HEN04103L/HEN08103L




HEN04103L/HEN08103L




## DIMENSIONS

HEN16103L/ HEN32103L



HEN16103L/ HEN32103L



# 4-/8-/16-/32-Channel ENVRs

## TECHNICAL SPECIFICATIONS

| OPERATIONAL                   |   |
|-------------------------------|---|
| MAIN PROCESSOR                | Quad-core embedded processor  |
| OPERATING SYSTEM              | Embedded LINUX  |
| VIDEO                         |   |
| INPUTS                        | <b>HEN04103L:</b> 4 Channels IP<br><b>HEN08103L:</b> 8 Channels IP<br><b>HEN16103L:</b> 16 Channels IP<br><b>HEN32103L:</b> 32 Channels IP  |
| AUDIO                         |   |
| AUDIO INPUT/OUTPUT            | 1 Channel Input/1 Channel Output, RCA   |
| TWO-WAY COMMUNICATION         | Supported   |
| OPERATIONAL                   |   |
| INTERFACE                     | 1 HDMI, 1 VGA   |
| RESOLUTION                    | 3840 × 2160; 1920 × 1080;<br>1280 × 1024; 1280 × 720;   |
| DISPLAY SPLIT                 | <b>HEN04103L:</b> 1/4<br><b>HEN08103L:</b> 1/4/8/9<br><b>HEN16103L/ HEN32103L:</b> 1/4/8/9/16   |
| OSD                           | Camera title; Time; Video loss; Camera lock;<br>Motion detection; Recording   |
| OPERATIONAL                   |   |
| COMPRESSION                   | H.265/H.264   |
| RESOLUTION                    | <b>8 MP</b> (3840 × 2160); <b>6 MP</b> (3072 × 2048);<br><b>5 MP</b> (2560 × 1920); <b>4 MP</b> (2560 × 1440);<br><b>3 MP</b> (2048 × 1520); <b>1080p</b> (1920 × 1080);<br><b>720p</b> (1280 × 720); <b>D1</b> (704 × 576/704 × 480);<br><b>CIF</b> (352 × 288/ 352 × 240) |
| FRAME RATE                    | 1–15 fps (8 MP); 1–25/30 fps (rest of the resolutions) for each channel   |
| RECORD BIT RATE               | <b>HEN041*3:</b> 80Mbps<br><b>HEN081*3:</b> 200Mbps<br><b>HEN161*3:</b> 200Mbps   |
| BIT RATE <sup>1</sup>         | 16 kbps ~ 20 Mbps, per channel  |
| RECORDING MODE                | Schedule (Regular/Continuous, Motion Detection, Alarm); Manual; Stop  |
| RECORDING INTERVAL            | 1 to 120 minutes (default 60 min)   |
| PRE-EVENT RECORDING INTERVAL  | 1 to 30 seconds   |
| POST-EVENT RECORDING INTERVAL | 10 to 300 seconds   |
| VIDEO DETECTION AND ALARMS    |   |
| TRIGGER EVENTS                | Recording; PTZ; Tour; Alarm; Video Push; Email; FTP; Snapshot; Buzzer; Screen Tips  |
| VIDEO DETECTION               | Motion Detection—MD Zones: 396 (22 × 18);<br>Video Loss; Tampering  |
| ALARM INPUT                   | 4 Channels  |
| RELAY OUTPUT                  | 2 Channels  |
| STORAGE                       |   |
| INTERNAL HDD                  | <b>HEN16103L/ HEN32103L:</b> 2 SATA III ports, up to 12 TB<br><b>HEN04103L/HEN08103L:</b> 1 SATA III Port (up to 6 TB)  |
| PLAYBACK AND BACKUP           |   |
| SYNC PLAYBACK                 | 4-channel NVRs: 1/4<br>8-channel NVRs: 1/4/8<br>16-channel NVRs: 1/4/8/16<br>32-channel NVRs: 1/4/8/16  |
| DECODING                      | 2-ch in 8 MP@15pfs or 4-ch in 1080P@30fps   |
| SEARCH MODE                   | Time/Date; Alarm; Motion Detection (MD); Exact Search (accurate to a second); Smart Search  |
| PLAYBACK FUNCTION             | Play; Pause; Stop; Rewind; Fast play; Slow play; Next File; Previous File; Next Camera; Previous Camera; Full Screen; Repeat; Shuffle; Backup Selection; Digital Zoom   |
| BACKUP MODE COMPATIBILITY     | USB Device; Network   |

| NETWORK                          |   |
|----------------------------------|---|
| ETHERNET                         | 1 RJ-45 port (10/100/1000 Mbps)   |
| POE                              | N/A   |
| SUPPORTED PROTOCOLS <sup>2</sup> | HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search, P2P                                |
| MAXIMUM NUMBER OF USERS          | 128 users   |
| NETWORK THROUGHPUT               | <b>HEN04103L/HEN08103L:</b> 80 Mbps<br><b>HEN16103L/ HEN32103L:</b> 200 Mbps  |
| SMART PHONE COMPATIBILITY        | iPhone; iPad; Android   |
| AUXILIARY INTERFACE              |   |
| USB PORTS                        | <b>HEN04103L/HEN08103L:</b> 2 USB Ports (2 USB2.0)<br><b>HEN16103L/HEN32103L:</b> 2 USB Ports (1 USB2.0, 1 USB3.0)  |
| RS232                            | 1 port (for POS communications)   |
| ELECTRICAL                       |   |
| POWER SUPPLY                     | <b>HEN04103L/HEN08103L:</b> DC12V/2A<br><b>HEN16103L/HEN32103L:</b> DC12V/4A  |
| POWER CONSUMPTION                | <b>HEN04103L/HEN08103L:</b> <6.3W (Without HDD)<br><b>HEN16103L/HEN32103L:</b> <6.9W (Without HDD)  |
| ENVIRONMENTAL                    |   |
| OPERATING TEMPERATURE            | -10°C ~ +55°C (+14°F ~ +131°F), 86 ~ 106kpa   |
| RELATIVE HUMIDITY                | 0% to 90% relative humidity   |
| STORAGE TEMPERATURE              | -4°F to 158°F (-20°C to 70°C)   |
| PHYSICAL                         |   |
| DIMENSIONS                       | <b>HEN16103L/HEN32103L:</b> 1U, 375mm×281.5mm×56mm (14.8" x 11.1" x 2.2")<br><b>HEN04103L/HEN08103L:</b> Compact 1U, 260mm×224.9mm×47.6mm (10.2" x 8.9" x 1.9") |
| WEIGHT (WITHOUT HDD)             | <b>HEN16103L/HEN32103L:</b> 1.6kg (3.5 lb) (without HDD)<br><b>HEN04103L/HEN08103L:</b> 0.8kg (1.76 lb) (without HDD)   |
| REGULATORY                       |   |
| EMISSIONS                        | FCC Part 15B, EN55032: 2012+AC: 2013  |
| IMMUNITY                         | EN50130-4: 2011   |
| SAFETY                           | EU: EN60950-1<br>North America UL listed to UL/CSA 60950-1  |
| ROHS                             | EN50581: 2012   |

- Actual bitrate is scene and motion dependent with H.264 stream.
- Some development might be required in specific user cases to support some of these protocols in the field, as protocols will mature over time.

# 4-/8-/16-/32-Channel ENVRs

## ORDERING

| ACCESSORIES            |            | RECOMMENDED CAMERAS               |   |
|------------------------|------------|-----------------------------------|---|
| <b>RACK MOUNT TRAY</b> | HENHQATRAY | <b>MINIDOME IP CAMERAS</b>        | H4D3PRV2, H4W2PRV2, H4W4PRV2, H2W2PRV3, H2W4PRV3, H4D3PRV3, H4W4PRV3, H4D8PR1, H4W4PER2, H4W4PER3     |
|                        |            | <b>BULLET IP CAMERAS</b>          | HBD3PR2, HBW2PR2, HBW4PR2, HBW4PER2, HBW2PR1, HBD8PR1, HBD2PER1, HBW4PER1, HBD1PR1, HBD3PR1           |
|                        |            | <b>IR PTZ IP CAMERAS</b>          | HDZP252DI, HDZP304DI  |
|                        |            | <b>BALL/MICRO DOME IP CAMERAS</b> | HEW2PRW1, HEW4PRW3, HED8PR1, HED2PER3, HEW4PER3, HEW2PR1, HEW4PR3, HEW2PR2, HEW4PR2, HED1PR3, HED3PR3 |

| ORDERING         |  |
|------------------|--|
| <b>HEN04103L</b> | H.265 4CH NVR, OTB, NO POE, 4k, output HDMI/VGA 4k, Ethernet Gigabit, 4 inputs/2 outputs     |
| <b>HEN08103L</b> | H.265 8CH NVR, OTB, NO POE, 4k, output HDMI/VGA 4k, Ethernet Gigabit, 4 inputs/2 outputs     |
| <b>HEN16103L</b> | H.265 16CH NVR, OTB, NO POE, 4k, output HDMI/VGA 4k, Ethernet Gigabit, 4 inputs/2 outputs    |
| <b>HEN32103L</b> | H.265 4K 32CH NVR, OTB, NO POE, 4k, output HDMI/VGA 4k, Ethernet Gigabit, 4 inputs/2 outputs |

**For more information, please contact:**

Email: [hsf.comms@honeywell.com](mailto:hsf.comms@honeywell.com)  
HBT: [buildings.asean@Honeywell.com](mailto:buildings.asean@Honeywell.com)  
HSF: [hsf.comms@honeywell.com](mailto:hsf.comms@honeywell.com)  
Partner Connect Portal:  
[www.partnerconnect.honeywell.com](http://www.partnerconnect.honeywell.com)  
Order management:  
[customersupportHSFASEAN@honeywell.com](mailto:customersupportHSFASEAN@honeywell.com)

**Technical support call centre (small and medium businesses)**

Vietnam: +84 4 4458 3369  
Thailand: +66 2 0182439  
Indonesia: +62 21 2188 9000  
Malaysia: +603 7624 1530  
Singapore: +65 3158 6830  
Philippines: +63 2 231 3380

**Honeywell International Philippines Inc.**

Figari Serviced Office, Level 11 Suite C,D,E  
The Curve BGC (Figari Serviced Office)  
32nd corner 3rd Avenue, Bonifacio Global City, Taguig  
City  
Philippines 1634

**PT. Honeywell Indonesia**

Menara Prima, 23rd Floor  
Jl. DR. Ide Anak Agung Gde Agung Blok 6.2  
Kawasan Mega Kuningan  
Jakarta 12950  
Indonesia

**Honeywell Thailand**

252/121 25th Floor  
Muang Thai-Phatra office Tower II  
Ratchadapisek Road, Huay Khwang  
Bangkok 10320  
Thailand

**Honeywell Malaysia**

Honeywell International Sdn Bhd,  
Level 25, UOA Corp Tower, Lobby B,  
Avenue 10, The Vertical, Bangsar South City,  
59200, Kuala Lumpur, Malaysia

**Honeywell Singapore**

Honeywell Pte Ltd  
17 Changi Business Park Central 1  
Honeywell Building  
Singapore 486073

**Honeywell Vietnam Co.Ltd.**

Suite 1405-1408, 14 Floor, Pacific Place,  
83B Ly Thuong Kiet, Hoan Kiem District, Hanoi  
Vietnam

**Honeywell Vietnam Co.Ltd**

Unit 11, 5 Floor, Crescent Plaza,  
105 Ton Dat Tien Street, Tan Phu Ward, District 7, HCMC  
Vietnam

**Honeywell Singapore**

Honeywell Pte. Ltd.  
17 Changi Business Park Central 1  
Honeywell Building, Singapore 486073

**Honeywell Myanmar**

No. 35, U Kyaw Hla Street, 7th Mile,  
Mayangone Township, Yangon 11061  
Myanmar

Honeywell reserves the right, without  
notification, to make changes in  
product design or specifications.

HSV-HENx3L-01-EN(0418)DS-E  
© 2018 Honeywell International Inc.